

~~POSTERIORI-BUS TRACE ANALYSIS~~

BACKGROUND OF THE INVENTION

1. Technical Field:

The present invention is directed toward analyzing  
5 trace data from a logic analyzer. In particular the present  
invention is directed toward identifying and summarizing  
packets sent over a bus system.

2. Description of Related Art:

Computer system design, initialization and integration  
10 activities often can include probing and collecting of bus  
trace data. Raw bus trace data is difficult to analyze when  
in numeric or signal form. In particular, when activity on  
a bus system involves the exchange of variable-length  
packets, the raw trace data is particularly difficult to  
15 decipher.

Logic analyzers are frequently used to acquire bus  
trace data. Logic analyzers may also be programmed to  
perform some analysis of the raw data, but this capability  
is often limited, both in the complexity of transactions to  
20 be analyzed and in the bus speeds for which real-time  
analysis is possible.

It would be advantageous, therefore, to be able to  
analyze bus transactions of arbitrary length and complexity  
using trace data acquired at any speed at which raw trace  
25 data may be acquired.

FOIA b 7 - EXEMPT

Docket No. AUS920010404US1

## SUMMARY OF THE INVENTION

The present invention provides a method, computer program product, and data processing system for analyzing trace data containing bus transactions taking place in packets of varying length. A dump of raw trace data from a logic analyzer is stored in a computer file. A computer program then analyzes the raw trace data to identify the locations of packets within the raw trace data. A packet type is determined for each packet, and data fields are extracted from the packet, according to the packet type. A summary of each packet containing the data fields and their contents is then presented to a user.

**BRIEF DESCRIPTION OF THE DRAWINGS**

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**Figure 1** is a diagram containing an overall view of the hardware used in a preferred embodiment of the present invention;

**Figure 2** is a block diagram of a data processing system in which the processes of the present invention may be implemented;

**Figure 3** is a timing diagram describing a process of transmitting a packet over a bus system under test by a preferred embodiment of the present invention;

**Figures 4A and 4B** are timing diagrams depicting clock signals used to trigger a logic analyzer in accordance with a preferred embodiment of the present invention;

**Figure 5** is a diagram depicting the bit vectors generated by a logic analyzer and transmitted to a computer workstation in a preferred embodiment of the present invention;

**Figure 6** is a diagram depicting a typical packet monitored for in a preferred embodiment of the present invention;

**Figure 7** is a diagram depicting a typical summary output by a preferred embodiment of the present invention;

**Figure 8** is a flowchart representation of a basic process of a posteriori analyzing trace data in accordance with a preferred embodiment of the present invention; and

Docket No. AUS920010404US1

**Figure 9** is a more detailed flowchart representation of a process of analyzing trace data in accordance with a preferred embodiment of the present invention.

0599837-111501  
TTTT " 28E8550

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

**Figure 1** is a diagram providing an overall view of the hardware involved in a preferred embodiment of the present invention. A logic analyzer **100** reads signals from a bus system on a circuit board **102** to create a sequence of bit vectors. A bit vector is an ordered set of bits representing the state of a set of signals within a digital circuit at a particular point in time. The bit vectors obtained by logic analyzer **100** are transmitted to computer workstation **104**.

Computer workstation **104** first stores the bit vectors in a file. Computer workstation **104** then executes an analysis program to interpret the bit vectors. Bit vectors are simply raw binary data. In a preferred embodiment of the present invention, however, the raw bit vectors represent packets of information in a bus system. Computer workstation **104** identifies where in the sequence of bit vectors these packets begin and end. Computer workstation **104** then identifies where certain fields of data exist within each of the packets and reports these data fields to a user.

With reference now to **Figure 2**, a block diagram of a data processing system is shown in which the present invention may be implemented. Data processing system **200** is an example of a computer, such as computer workstation **104** in **Figure 1**, in which code or instructions implementing the processes of the present invention may be located. Data processing system **200** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used. Processor **202** and

Docket No. AUS920010404US1

main memory **204** are connected to PCI local bus **206** through PCI bridge **208**. PCI bridge **208** also may include an integrated memory controller and cache memory for processor **202**. Additional connections to PCI local bus **206** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **210**, small computer system interface SCSI host bus adapter **212**, and expansion bus interface **214** are connected to PCI local bus **206** by direct component connection. In contrast, audio adapter **216**, graphics adapter **218**, and audio/video adapter **219** are connected to PCI local bus **206** by add-in boards inserted into expansion slots. Expansion bus interface **214** provides a connection for a keyboard and mouse adapter **220**, modem **222**, and logic analyzer interface **224**. SCSI host bus adapter **212** provides a connection for hard disk drive **226**, tape drive **228**, and CD-ROM drive **230**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **202** and is used to coordinate and provide control of various components within data processing system **200** in **Figure 2**. The operating system may be a commercially available operating system such as Windows 2000, which is available from Microsoft Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provides calls to the operating system from Java programs or applications executing on data processing system **200**. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented programming system, and applications or

Docket No. AUS920010404US1

programs are located on storage devices, such as hard disk drive **226**, and may be loaded into main memory **204** for execution by processor **202**.

Those of ordinary skill in the art will appreciate that  
5 the hardware in **Figure 2** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash ROM (or equivalent nonvolatile memory) or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure**  
10 **2**. Also, the processes of the present invention may be applied to a multiprocessor data processing system. For example, data processing system **200**, if optionally configured as a network computer, may not include SCSI host bus adapter **212**, hard disk drive **226**, tape drive **228**, and  
15 CD-ROM **230**, as noted by dotted line **232** in **Figure 2** denoting optional inclusion. In that case, the computer, to be properly called a client computer, must include some type of network communication interface, such as LAN adapter **210**, modem **222**, or the like. As another example, data processing  
20 system **200** may be a stand-alone system configured to be bootable without relying on some type of network communication interface, whether or not data processing system **200** comprises some type of network communication interface. As a further example, data processing system **200**  
25 may be a personal digital assistant (PDA), which is configured with ROM and/or flash ROM to provide non-volatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 2** and above-described  
30 examples are not meant to imply architectural limitations. For example, data processing system **200** also may be a notebook computer or hand held computer in addition to

0993337 11501  
10511 233660

Docket No. AUS920010404US1

taking the form of a PDA. Data processing system **200** also may be a kiosk or a Web appliance.

The processes of the present invention are performed by processor **202** using computer implemented instructions, which  
5 may be located in a memory such as, for example, main memory **204** or in one or more peripheral devices **226-230**.

Logic analyzer interface **224** provides a connection to a logic analyzer, such as logic analyzer **100** in **Figure 1**. Computer **200** can download bit vectors or other analyzer  
10 trace data from the logic analyzer to be stored in memory **204** or hard disk drive **226**, for instance. In a preferred embodiment of the present invention, computer **200** downloads bit vectors to a file on hard disk drive **226**, then executes an analysis program to analyze the bit vector data a  
15 posteriori.

**Figure 3** is a timing diagram depicting the transmission of a packet over a bus system in a circuit board under test in a preferred embodiment of the present invention. The bus system signals comprise a clock signal **300**, a plurality of  
20 data lines **302**, and a flag signal **304**. Clock signal **300** times the transmission of data across the bus system. Data lines **302** carry binary data in parallel over the bus system. Typically, data lines **302** will comprise eight, sixteen, or thirty-two data lines representing eight, sixteen, or  
25 thirty-two bits of data transmitted across the bus system at any one time. Flag signal **304** signals the beginning and ending of packets over the bus. Typically, flag signal **304** will be at high level (logic 1) while the data packet is being transmitted, and will return to low level (logic 0)  
30 (**306**) a few clock cycles before the data packet transmission ends (**308**).

**Figures 4A** and **4B** are diagrams depicting a clock signal used for triggering logic analyzer **100**. Logic analyzer **100** reads a series of bit vectors from circuit board **102** over

FILED "23E35650



Docket No. AUS920010404US1

time. Timing signal **401** (**Figure 4A**), which corresponds with clock signal **400** in **Figure 4**, triggers the acquisition of bit vector values from circuit board **102**. **Figure 4A** depicts a mode of operation of logic analyzer **100** in which bit  
5 vectors are read at each rising edge (**400, 402**) of clock signal **401**. **Figure 4B** depicts a mode in which bit vectors are read on each rising edge and falling edge (**404, 406, 408, 410**). In the preferred embodiment herein described, it is necessary to read bit vectors at both rising and falling  
10 edges of the clock signal.

With many logic analyzers, however, operation at higher speeds (i.e., higher clock speeds or triggering on both edges of the clock signal) means that the functionality of the logic analyzer becomes reduced. An analyzer that might  
15 be able to detect patterns in the bit vectors at 250 MHz, may not be able to detect such patterns at 500 MHz, for instance. This is at least part of the motivation for the present invention. The present invention allows for a posteriori analysis of trace data, which can be performed  
20 regardless of what speeds of operation the logic analyzer is capable of operating at.

**Figure 5** is a diagram depicting the bit vectors generated by logic analyzer **100** and transmitted to computer workstation **104** in a preferred embodiment of the present  
25 invention. Bit vectors **500** are downloaded to computer workstation **104** and preferably stored in a text file wherein each line of the text file represents a single bit vector. **Figure 5** depicts a text file in accordance with the bus system signals shown in **Figure 3**.

Thus, the first bit of each vector (**502**) represents a clock signal. One can see that the value of clock bit **502** changes with each vector, since logic analyzer **100** is configured to trigger the reading of a bit vector on both edges of clock signal **300**. The middle eight bits (**504**)  
35 represent bytes of data. Finally, the last bit of each

09998877 11501  
T05T 288660

Docket No. AUS920010404US1

vector (506) represents the state of flag signal 304. The beginning and end of a packet are identified using flag bit 506. A transition in flag bit 506 from zero to one denotes the beginning of a packet, and the end of a packet is

5 signified by transitioning flag bit 506 back to zero a few bytes before the end of the packet. How many bytes before the end of the packet the transition occurs at depends on the length of the packet in a preferred embodiment of the present invention. This is described in more detail in

10 **Figure 9.**

**Figure 6** is a diagram depicting a typical packet 600 in a preferred embodiment of the present invention. Packet 600 is made up of a series of 16-bit words 601, which are themselves decomposed into two 8-bit bytes 602 and 604, for

15 transmission over an 8-bit bus system. Each of words 601 is divided into data fields, such as packet type data field 606. Each different type of packet will contain different fields, and different packets may have different lengths. The length of the packet, as was stated earlier, is

20 determined by a flag signal. Packet type data field 606 denotes the packet type, which identifies the particular set of data fields present within packet 600.

Analysis software executed by computer workstation 104 (**Figure 1**) takes the raw bit vector data shown in **Figure 5**,

25 identifies the presence of packets within the data, identifies the fields within each packet, and finally outputs a summary of the packet contents for a user. **Figure 7** is a diagram depicting a typical summary output by a preferred embodiment of the present invention. Cycle line

30 700 provides an identifier number for identifying the packet being described. Lines 702 list various fields of the packet and their contents.

**Figure 8** is a flowchart representation of the basic process of a posteriori analyzing trace data in accordance

35 with a preferred embodiment of the present invention. Bit

099937-11501  
FOSTF 282660

vectors of trace data are read in from a file (step 800). A packet is identified within the trace data (step 802). Data fields are extracted from the packet data (step 804). Finally, the fields are reported to a user (step 806), before the process cycles again to step 800 to read additional vectors from the file.

Vectors of trace data (representing bytes transferred across the bus system under test) are read in while the flag bit is set to one, until the flag bit is transitioned to zero (step **900**). If two vectors with flag bit set to one were reads (step **902:Yes**), then a "sync" packet for synchronizing bus peripherals and processor(s) has been encountered, and a the next contiguous block of thirteen zero bytes should be read in as the sync packet before proceeding (step **904**). The process then cycles to step **900** to read additional vectors.

Once a packet has been read in, the packet's type is identified (step **914**). Then, the specific fields corresponding to that particular type of packet are read in

Docket No. AUS920010404US1

from the packet (step 916). Finally, the fields and their contents are reported to a user (step 918) and the process cycles back to step 900 to read additional vectors.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. For instance, in one embodiment, packets may be read into memory one at a time to save memory space. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.